



Tyvek.

DUPONT™ TYVEK® FLEXWRAP™ NF



DuPont™ FlexWrap™ NF addresses the issues of flashing vulnerable bottom corners of the sill where water damage is most likely to occur.

An integral component of DuPont Weatherization Systems, DuPont™ FlexWrap™ NF is a conformable, self-adhesive flashing solution for sills and non-straight portions of windows, doors and other wall penetrations.

DuPont™ FlexWrap™ NF is a premium performance, extendable self-adhered flashing material that can be applied over a wide range of building substances, including non-nailable sheathing materials like PS foam board, fiberboard, concrete masonry unit (CMU) and other such materials. Unlike competitive products, DuPont™ FlexWrap™ NF does not require the use of mechanical fasteners in the flexed corner areas.

DuPont™ FlexWrap™ NF also flashes round-top or custom-shaped windows in a seamless manner, eliminating the need to cut and place individual pieces of conventional flashing on an arched opening.

BENEFITS

Superior protection from water damage

- Helps seal the building envelope when used with DuPont Weatherization Systems products
- Meets the AAMA 711-13 material standard at the highest classification levels: Class A (no primer) and Level 3 Thermal Exposure (80°C / 176°F for 7 days)
- Meets and Exceeds ASTM E331 Standard Test Method for Water Penetration of Exterior Windows, Skylights, Doors, and Curtain Walls by Uniform Static Air Pressure Difference: no leakage at 300 Pa (equivalent to 50 mph windload), even after thermal aging (0-120°F)
- Does not contain asphaltic / bitumen adhesive materials which many window manufacturers prohibit due to adverse material reactions, such as black staining, oozing, and deformation over time, particularly with vinyl flanges.
- Can be installed at external temperatures as low as -4°C (25°F) as long as the surface is clean and free from frost and ice

Easy installation

- Packaged in ready-to-use 6", 9" x 75 ft rolls or 9" x 15 ft rolls
- Helps to facilitate the creation of airtight and water tight seals around windows, door sills, chimney breasts, pipe penetrations, and any custom shapes.

Superior durability

- Extendable flashing constructed with a durable, micro-creped DuPont™ Tyvek® top-sheet, a premium butyl adhesive layer, and a specially designed release liner
- Designed to withstand up to 270 days of UV exposure

Excellent adhesion performance

- 100% butyl adhesive performs through extreme temperatures
- Adheres to most common building materials



DUPONT™ FLEXWRAP™ NF

THE DUPONT™ BUILDING KNOWLEDGE CENTER

All DuPont building envelope systems products are backed by industry-leading building science and unrivaled industry support provided by The DuPont™ Building Knowledge Center, your source for the DuPont product information and technical support you need to build quality, durable and energy-efficient structures.

DUPONT™ TYVEK® SPECIALIST NETWORK

A national group of highly trained field representatives is available to assist you with your installations. From the latest updates on building codes, to keeping up with current trends and challenges, your local DuPont™ Tyvek® Specialist can provide on-site consulting and training to help make sure the job gets done right.



DUPONT™ TYVEK® CERTIFIED INSTALLERS

The DuPont™ Tyvek® Certified Installer Network is one more way to put the building science expertise of DuPont right at your fingertips. Your DuPont™ Tyvek® Certified installer provides trained installation services to help seal the building envelope.

LIMITED WARRANTY

DuPont™ FlexWrap™ NF is backed by a limited warranty. To learn more about the system that's right for you and to contact a DuPont™ Tyvek® Specialist in your area, visit www.weatherization.tyvek.com or call 1-800-44-Tyvek.

COMPLETE SYSTEM OF PRODUCTS

For optimal protection on all your building projects, use DuPont™ FlexWrap™ NF with the complete line of DuPont building envelope systems products, including:

Building Wraps:

- DuPont™ Tyvek® HomeWrap®
- DuPont™ Tyvek® StuccoWrap®
- DuPont™ Tyvek® DrainWrap™
- DuPont™ Tyvek® ThermaWrap® R5.0
- DuPont™ Tyvek® ThermaWrap® LE

Flashing Systems:

- DuPont™ FlexWrap™ NF
- DuPont™ StraightFlash™
- DuPont™ StraightFlash™ VF
- DuPont™ Flashing Tape

Accessories:

- DuPont™ Tyvek® Tape
- DuPont™ Residential Sealant
- DuPont™ Tyvek® Wrap Caps
- DuPont™ Adhesive/Primer
- DuPont™ Window & Door Foam
- DuPont™ RainVent™ Battens

Roofing Underlayments:

- DuPont™ Tyvek® Protec™ 120
- DuPont™ Tyvek® Protec™ 160
- DuPont™ Tyvek® Protec™ 200

For more information about DuPont™ Tyvek® FlexWrap™ NF, please call 1-800-44-Tyvek or visit us at www.weatherization.tyvek.com



Proud Member